



AKUSTISK VARFÖR SERIES



Type:

Project:

Part Number:



Features:

- *Acoustic Suspended*
- *Acoustic Direct, Direct/Indirect, optics*
- *CETL Certified*
- *5 Year Warranty*
- *90+ CRI*
- *Colour temp available: 30K, 35K, 40K*
- *0-10V Dimming*
- *Damp Location Rated*

Ordering information (standard)

PART NUMBER	WATTS	CCT	EFFICACY	LUMENS
AK-VARFÖR-40W-XX-SP-XX-D	40W	30K,35K,40K	105 LM/W	4200 lm
AK-VARFÖR-50W-XX-SP-XX-D/I	50W	30K,35K,40K	105 LM/W	3675 lm Dir/1575 lm Ind
AK-VARFÖR-80W-XX-SP-XX-D	80W	30K,35K,40K	105 LM/W	8400 lm
AK-VARFÖR-100W-XX-SP-XX-D/I	100W	30K,35K,40K	105 LM/W	7350 lm Dir/3150lm Ind
AK-VARFÖR-120W-XX-SP-XX-D	120W	30K,35K,40K	105 LM/W	12600 lm
AK-VARFÖR-140W-XX-SP-XX-D/I	140W	30K,35K,40K	105 LM/W	10500 lm Dir/4200 lm Ind


SPECIFICATION

INPUT VOLTAGE 100-277V AC

DIMMABLE
ON-OFF, TRIAC, 0-10V

HOUSING COLOR: WH/BK STANDARD
**VARIOUS FINISHES AVAILABLE PLEASE SEE
ACOUSTIC COLOUR CHART BELOW

AKUSTISK VARFÖR SERIES





Ordering information

MODEL	WATTS	CONFIGURATION	MOUNTING	CCT	DISTRIBUTION	VOLTAGE	FINISH COLOUR	DIMMING
AK-VARFÖR	40W/50W*	ACO - ACOUSTIC	SP - SUSPENDED	30K	D - DIRECT	UNV - 120V	WH - WHITE	D - 0-10V DIMMING
	80W/100W*	BLANK - STANDARD		35K	D/I - DIRECT/INDIRECT		BK - BLACK	
	120W/140W*			40K			NSAC-XXX-XXX**	


*WATTAGE IS FOR D/I - DIRECT/INDIRECT OPTION ONLY - 50W(35W DIRECT/15W INDIRECT) 80W (70W DIRECT/30W INDIRECT) 140W (100W DIRECT/40W INDIRECT)

**WH/BK IS THE STANDARD FINISH - NSAC CODES BELOW DENOUCE FINISH COLOUR


Acoustic Colour List



Model No	A	B	C	L	H
AK-VARFÖR-40W-SP-XX-D	19.7"(500mm)	22.2"(563mm)	1.97"(50mm)	11.8"(300mm)	3.0"(75mm)
AK-VARFÖR-80W-SP-XX-D	37.9"(960mm)	42.6"(1082mm)	1.97"(50mm)	23.6"(600mm)	3.0"(75mm)
AK-VARFÖR-120W-SP-XX-D	56.1"(1425mm)	63.0"(1600mm)	1.97"(50mm)	35.4"(900mm)	3.0"(75mm)



Model No	A	B	C	L	H
AK-VARFÖR-40W-SP-XX-D/I	19.7"(500mm)	22.2"(563mm)	1.97"(50mm)	11.8"(300mm)	3.5"(90mm)
AK-VARFÖR-80W-SP-XX-D/I	37.9"(960mm)	42.6"(1082mm)	1.97"(50mm)	23.6"(600mm)	3.5"(90mm)
AK-VARFÖR-120W-SP-XX-D/I	56.1"(1425mm)	63.0"(1600mm)	1.97"(50mm)	35.4"(900mm)	3.5"(90mm)



Model No	A	B	C	L	H
AK-VARFÖR-XX-ACO-SP-XX	19.7"(500mm)	22.2"(563mm)	1.97"(50mm)	11.8"(300mm)	7.4"(188mm)
AK-VARFÖR-XX-ACO-SP-XX	37.9"(960mm)	42.6"(1082mm)	1.97"(50mm)	23.6"(600mm)	7.4"(188mm)
AK-VARFÖR-XXX-ACO-SP-XX	56.1"(1425mm)	63.0"(1600mm)	1.97"(50mm)	35.4"(900mm)	7.4"(188mm)